

Data for the Month:

April 2016

Data published:

May 2016

Basin ID	Date of Discharge	pH (unit)	Oil and Grease (Visibility)	TSS (mg/L)	*NTU	Comment
TB1112L	1/04/2016	7.9	NV		20	
TB1252L	1/04/2016	7.9	NV		20	
TB1252L	4/04/2016	8	NV		45	
PB838L	12/04/2016	7.2	NV		30	
TB749L	11/04/2016	7.3	NV		18	
TB1252L	11/04/2016	7.1	NV		40	
TB1227L	11/04/2016	7.5	NV	42	25	#Lab sample collected
TB895R	11/04/2016	6.8	NV		<20	
TB1079L	12/04/2016	7.1	NV		<20	
TB680L	13/04/2016	7.5	NV		<20	
TB1112L	13/04/2016	7.5	NV		<20	
TB1285L	13/04/2016	7.2	NV		<20	
TB1112L	13/04/2016	7.5	NV		<20	
PB624R	14/04/2016	7.8	NV		35	
TB820L	14/04/2016	6.8	NV	15	30	#Lab sample collected
PB571R	14/04/2016	7.3	NV		38	
PB572L	15/04/2016	7.3	NV		<20	
PB38L	14/04/2016	7.4	NV		36	
Hawthorne Pad	16/04/2016	7.7	NV	5	<20	#Lab sample collected
TB512R	16/04/2016	7.5	NV		<20	
KTR Office	16/04/2016	7.6	NV		20	
PB27L	16/04/2016	7.6	NV		<20	
PB82L	16/04/2016	7.1	NV		30	
TB278R	19/04/2016	8.4	NV		35	
PB479R	22/04/2016	8.2	NV		18	
PB27L	22/04/2016	7.7	NV		40	
PB82L	22/04/2016	7.8	NV		30	
TB680L	22/04/2016	7.6	NV		<20	
Hawthorne Pad	27/04/2016	7.1	NV	20	<20	#Lab sample collected
TB512R	27/04/2016	7.3	NV		30	
PB479R	27/04/20016	7.2	NV		<20	
KTR stockpile	27/04/2016	7.1	NV		37	
TB1322L	28/04/2016	7.6	NV		40	
PB838L	28/04/2016	7.2	NV		39	
PB27L	28/04/2016	7.4	NV		40	
KTR Office	28/04/2016	7.4	NV		26	



Data for the Month: April 2016

Data published: May 2016

TB1375L	28/04/2016	7.6	NV	35	
PB624R	29/04/2016	8	NV	25	
PB163L	29/04/2016	8.2	NV	30	
PB135L	29/04/2016	8	NV	35	
TB1112L	30/04/2016	7.9	NV	<20	
TB1079L	30/04/2016	8.1	NV	7	#Lab sample collected
TB1285L	30/04/2016	7.1	NV	<20	
PB479R	30/04/2016	7.5	NV	30	

Pollutant	TSS	*NTU	pH	Oil and Grease
Concentration Limit	50	60	6.5 – 8.5	Not visible

mg/L = milligrams per litre N/A = Not applicable NV = Not visible NC = Non-Conformance ND = No Discharge DNS = Did Not Sample TSS = Total Suspended Solids (mg/L)	*NTU = Nephelometric Turbidity Units A correlation between TSS and NTU has been established for the site. NTU reading of 60 has been adopted to ensure samples have a TSS of below 50mg/L. #1/10 Basin discharges to be lab tested for TSS; for correlation verification.
---	--